



PRODUCTS COMPANY

P.O. Box 1300 TRENTON, NJ 08607

TEL. (609) 394-0150 FAX (609) 989-4847

Material Safety Data Sheet

Page 1 of 6

Date: 5/9/07
Product Name: X-PANDO PIPE JOINT COMPOUND
Product Description: Sealant for threaded and flanged pipe

1. Identification

X-Pando Products Company
500 Southard Street
Trenton, NJ 08638
U.S.A

For Product Information/Emergency Phone Number:
609-394-0150

Chemical Name or Synonym:
N/A

2. Hazards Identification

A. Emergency Overview:

Information Pertaining To Particular Dangers For Man And Environment:
NOT Hazardous according to criteria of NOHSC/ASCC

Physical Appearance:
Gray to black powder with no odor.

B. Potential Health Effects:

Acute Eye:
May cause mechanical irritation if exposed to large amounts of the dust.

Acute Skin:
This product may cause skin irritation.

Acute Inhalation:
May cause irritation to respiratory tract and lung damage if exposure is repeated or prolonged. Although unlikely, inhalation of fumes from heated material may cause metal fume fever, a flu-like illness characterized by delayed symptoms of cough, muscle pains chills and nausea.

Acute ingestion:
This product may cause gastrointestinal harm and nausea if it is swallowed.



Material Safety Data Sheet

Chronic Exposure:

Prolonged or repeated skin contact may cause burns. Prolonged inhalation of dust may lead to lung damage (pneumoconiosis). Symptoms include coughing, difficulty breathing, and the production of black sputum. Symptoms may be delayed until after years of exposure.

Aggravation of Pre-existing Conditions:

Individuals with pulmonary and/or respiratory disease, including, but not limited to, asthma and bronchitis, or subject to eye irritation should be precluded from exposure.

3. Composition/Information on Ingredients

Component	CAS#	%
Magnesium Oxide	1309-48-4	10-30
Graphite (synthetic)	7782-42-5	7-13
Magnesium Chloride	7791-18-6	15-40
Calcium Carbonate	1317-65-3	15-40
Starch Gum	9004-53-9	1-5
Non Hazardous Ingredients	NA	Balance

4. First Aid Measures

First Aid Measures for Accidental:

Eye Exposure:

Irrigate eyes with large amounts of water for at least 15 minutes, while holding the eyelid(s) open. Seek medical attention if irritation persists.

Skin Exposure:

Wash the affected area with soap and water. Seek medical attention if irritation persists.

Inhalation:

Move victim to fresh air and treat symptomatically.

Ingestion:

Contact local poison control center or physician IMMEDIATELY.

5. Fire Fighting Measures

Fire Hazard Data:

Autoignition: N/A

Flash Point: N/A

Material Safety Data Sheet

Page 3 of 6

Flammability Limits (vol/vol%):**Lower:**
N/A**Upper:**
N/A**Extinguishing Media:**

Use extinguishing media appropriate for surrounding fire.

Special Fire Fighting Procedures:

Use self contained breathing apparatus with full face mask.

Unusual Fire and Explosion Hazards:

Fire produces oxides of magnesium, calcium and carbon.

6. Accidental Release Measures

Cleanup and Disposal of Spill:

Vacuum or scoop spilled material and place in closed containers for disposal. Avoid dust generation. Dispose of waste in accordance with local, state and federal regulations.

7. Handling and Storage

Handling/Storage:

Avoid dust generation and wear proper personal protection equipment as identified in Section 8. Store in a closed container in dry area.

8. Exposure Controls / Personal Protection

Exposure Guidelines:

Component	ACGIH	OSHA-PELs
Magnesium Oxide	10 mg/m ³	15 mg/m ³ 5 mg/m ³ respirable dust
Graphite (synthetic)	2 mg/m ³	2 mg/m ³
Magnesium Chloride	5 mg/m ³	15 mg/m ³
Calcium Carbonate	10 mg/m ³	15 mg/m ³ 5 mg/m ³ respirable dust
Starch Gum	10 mg/m ³	15 mg/m ³
Non Hazardous Ingredients	NA	NA

Engineering Controls:

Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the MSDS.



PRODUCTS COMPANY

P.O. Box 1300 TRENTON, NJ 08607

TEL. (609) 394-0150 FAX (609) 989-4847

Material Safety Data Sheet

Page 4 of 6

Respiratory Protection:

Follow the OSHA respirator regulations found in 29CFR 1910.134 or European Standard EN 149. Always use a NIOSH or EN approved respirator when necessary.

Eye / Face Protection:

If eye contact while using product may be anticipated, wear appropriate safety glasses with side shields or chemical goggles as described by OSHA's eye and face protection regulations in 29CFR 1910.133 or European Standard EN166.

Skin Protection:

Wear chemical resistant, impervious gloves for routine industrial use. Use body protection appropriate for task. An apron or other impermeable body protection is suggested. Full-body chemical protective clothing is recommended for emergency response procedures.

9. Physical and Chemical Properties

Physical Appearance: Gray to Black powder

Odor: None

pH: NA

Specific Gravity/Density: 2.56

Water Solubility: Appreciable

Melting Point: N/A

Freezing Point: ND

Boiling Point: N/A

Vapor Pressure: ND

Percent Volatiles by Volume: ND

Evaporation Rate: ND

Viscosity: ND

Flash Point: N/A

Explosion Limits: Lower: N/A

Upper: N/A

Autoignition Temp: N/A

10. Stability and Reactivity

Chemical Stability:

Stable

Conditions to Avoid:

Dust generation

Materials / Chemicals to Be Avoided:

Avoid contact with strong acids and strong bases.

Hazardous Decomposition Products:

Hazardous decomposition products such as hydrogen chloride, chlorine and magnesium oxide fumes may develop with exposure to high temperatures.



PRODUCTS COMPANY

P.O. Box 1300 TRENTON, NJ 08607

TEL. (609) 394-0150 FAX (609) 989-4847

Material Safety Data Sheet

Page 5 of 6

Hazardous Polymerization:

Will not occur.

11. Toxicological Information

Acute Effects

For Magnesium Oxide: LD50 Mouse: 810 mg/kg

For Magnesium Chloride: LD50 Rat: 8100 mg/kg

Chronic Effects

Carcinogenicity: Not identified as a carcinogen by NTP, IARC or OSHA

Mutagenicity: No Data

Reproductive Effects: No Data

Developmental Effects: No Data

12. Ecological Information

Ecotoxicological Information:

Not Determined

13. Disposal Considerations

Waste Disposal Method:

Discard any product, residue, disposable container or liner in full compliance with national regulations.

Container Handling and Disposal:

Dispose of container and unused contents in accordance with national regulations.

14. Transportation Information

Shipping Name:

ADR/RID/IMO/ICAO /US DOT	Proper Shipping Name	Not Regulated
	Hazard Class	Not Regulated
	ID Number	Not Regulated
	Packaging Group	Not Regulated



PRODUCTS COMPANY

P.O. Box 1300 TRENTON, NJ 08607

TEL. (609) 394-0150 FAX (609) 989-4847

Material Safety Data Sheet

Page 6 of 6

15. Regulatory Information

U.S. Federal Regulations:

SARA Title III Hazard Classes:

Fire Hazard: No
Reactive Hazard: No
Release of Pressure: No
Acute Health Hazard: No
Chronic Health Hazard: No

TSCA

All components of this product are on the TSCA inventory or are not required to be listed.

Other Regulations:

None

16. Other Information

National Fire Protection Association NFPA(R) and Hazardous Materials Identification System (HMIS) Hazard Ratings –:

Health Hazard: 1
Flammability: 0
Reactivity: 0

Key Legend Information:

N/A – Not Applicable

ND – Not Determined

ACGIH – American Conference of
Governmental Industrial Hygienists

OSHA – Occupational Safety and Health
Administration

TLV – Threshold Limit Value

PEL – Permissible Exposure Limit

TWA – Time Weighted Average

STEL – Short Term Exposure Limit

NTP – National Toxicology Program

IARC – International Agency for Research on
Cancer

RTECS - Registry of Toxic Effects of Chemical
Substances